

## CONCRETE TEST HAMMER (Schmidt Hammer)

Code : B110



- Used to perform a non-destructive test on concrete structure.
- The hammer gives an immediate indication about the compressive strength of the structural element.
- The compressive strength range that can be read by the equipment is from 10 to 70 N/mm<sup>2</sup>

### Testing Anvil:

- Used to verify the calibration for the rebound test hammers for concrete.
- It's made of a very robust stainless steel.
- The rebound value is  $80 \pm 2$ .
- Standards recommend the use of the Anvil before any sequence of test using the test hammers. Before and after every sequence of tests, anvil value should be recorded.
- Specifications:
  - Rebound Value :  $80 \pm 2$

- Made of Stainless Steel

### **TECHNICAL SPECIFICATIONS**

- Used for Test Hammers
- Rebound Value :80 ± 2
- Made of Stainless Steel

### **SUPPLIED WITH**

- Carborundum Stone
- Carrying Case

### **TECHNICAL SPECIFICATIONS**

- Compressive Strength :10-70 N/mm<sup>2</sup>

### **ORDERING INFORMATION**

Item	Code
CONCRETE TEST HAMMER - ALFA	B110X001H
CONCRETE TEST HAMMER - Digital	B110X002B
CONCRETE TEST HAMMER - Italy	B110X002H
TESTING ANVIL	B110P001H

### **OTHER PHOTOS**

